

ELECTROSPINNING OF FIBRINOGEN NANOFIBERS

[Tatjana Sindelar](#)¹, [Lila Nikkola](#)², [Nurredin Ashammakhi](#)², Martijn van Griensven¹, [Heinz Redl](#)¹

¹ *Ludwig Boltzmann Institute for Experimental and Clinical Traumatology, Vienna, Austria*

² *Institute of Biomaterials, Tampere University of Technology, Tampere, Finland*

INTRODUCTION: Electrospinning has been recognized as an efficient technique for the fabrication of polymer nanofibers. It uses an electric field to control the deposition of polymer fibers onto a target substrate. This electrostatic processing strategy can be used to fabricate fibrous polymer mats composed of fiber diameter mostly between 100 nm and 3 μm . In this study we describe electrospinning of fibrinogen nanofibers in an attempt to create biomimicking tissue in vitro for use as a tissue scaffold.

METHODS: We have used lyophilized human fibrinogen of the product Tisseel[®] VH (Baxter AG, Austria) to demonstrate fibrinogen electrospinning. Fibrinogen dissolved in 1,1,1,3,3,3-hexafluoro-2-propanol and sodium chloride solution was electrospun under various conditions. Electrospun fibers of fibrinogen were processed for scanning electron microscopy (SEM) evaluation and analyzed by native gelelectrophoresis.

RESULTS: The SEM evaluation showed that formed fibers were flat and had large diameter distribution from 120-1000 μm resulting in approximate fiber diameter of 550 μm . With some conditions bead formation occurred.

DISCUSSION AND CONCLUSION: The efficacy of this process, as well as the final fiber product, are affected by many factors, including, but not limited to solution polymer concentration, viscosity of solution, voltage between solution and ground electrode, the distance between the Taylor cone and the ground electrode, and environmental conditions such as humidity and temperature. Nano fiber similarity in size to native extracellular matrix components and the 3-dimensional structure allows cells to attach to several fibers in a more natural geometry. In summary, the electrospinning process is a

simple and efficient technique for the fabrication of 3D structures composed of fibrinogen fibers.

ACKNOWLEDGEMENTS: This work is in the framework of the European Commission Network of Excellence (EXPERTTISSUES Project).